

"Abserver" vibration test

Test report

January 2008

Zen-Ei Shoji Co., Ltd.
Kanazawa Manufacturing Co., Ltd.
Tokyo Metropolitan College of Industrial Technology

0.Introduction

We started development of a seismic isolation device for computer racks, cultural properties and precious assets in order to protect them from huge earthquakes.

Upon development, we firstly vibrated random waves with a simplex vibration trestle on one axis to grasp the characteristics of the device, and decided the final specification for mass production.

In order to investigate the actual behavior at the time of the earthquake, we simulated the seismic waves actually observed at the Kobe Marine Weather Valley in the 1995 Hyogo ken Nanbu Earthquake on the 3D vibration table.

1.Test date and time

Test date and time : Tuesday, September 19, 2007 8: 00 ~ 18: 00

Test location: Urban Renaissance Agency

Urban Housing Technology Institute

2683 - 3 Ishikawacho, Hachioji City, Tokyo

tel 042-644-3751

<http://www.ur-net.go.jp/rd/vibrat/>



写真 1 - 1



写真 1 - 2

2. Shaking Table Specification

The specifications of the vibration table are shown below.

- Vibration direction Horizontal 2 axes,
vertical 1 axis, rotation around each axis
- Shaking table dimensions 4 m x 3 m
- Mounting load 4 tf
- Maximum displacement $X = \pm 250$ mm, $Y = \pm 200$ mm, $Z = \pm 100$ mm
- Maximum speed $X = \pm 75$ cm / s, $Y = \pm 75$ cm / s, $Z = \pm 75$ cm / s
- Maximum acceleration $X = \pm 1.2$ G, $Y = \pm 1.2$ G, $Z = \pm 1.2$ G
- Measuring device 64ch



写真 2 - 1




写真 2 - 2

3. Simulated seismic wave

The seismic waves to be excited on the vibrating table are the seismic waves measured at the Kobe Maritime Atmosphere for the Hyogo ken Nanbu (Kobe) Earthquake (magnitude: 7.3, depth of epicenter: about 18 km) occurred on January 17, 1995.

The north-south direction is vibrated in the X direction of the shaking table, and the east-west direction is vibrated in the Y direction.

Figure 3-1 shows the time history waveform of the actual acceleration.

Hyogo Nanbu (Kobe) earthquake the time history waveform of the actual acceleration

**Magnitude: 7.3,
Depth of epicenter: about 18 km**





Figure 3-1

3. Test equipment


As shown in Photo 3-1, "Abserver" was placed on the oscillating table, and the server rack was placed on it. Installed an accelerometer on the vibration table, Abserver top, and server rack top, and a displacement meter between the vibration table and Abserver to measure Abserver displacement.(Photo 3-1, Photo 3-2, Photo 3-3)



Acceleration on server rack
Photo 3-1



Accelerometer on Abserver
Photo 3-2



Measure of displacement of Abserver
Photo 3-3

5-1. Test result (acceleration)



For the calculation of the test, a low pass filter was used which was zero from 10 Hz to 20 Hz for the following reasons.

- For both X and Y directions, the numerical value of 10 Hz or more indicates an extremely small numerical value from the spectrum on the input side
- Accelerometer and displacement gauge Analogue value is A / D converted with Δt 0.005 sec (20 Hz)
- Consider the effect of the natural period of the rack loaded on Absverer









The excitation acceleration, the acceleration on the Absverer, the acceleration on the server rack, and the relative displacement of the Absverer are shown in the X direction and the Y direction, respectively.

	X direction (North-South)	Y direction (East-West)
Max. acceleration on Shaking table	1100 (gal)	692 (gal)
Max. acceleration on Absverer	156(gal) (1/7.1)	166(gal) (1/4.2)
Max. acceleration on the top of server rack	455(gal) (1/2.4)	532(gal) (1/1.3)
Max. displacement of Absverer	13.6 (cm)	11.1 (cm)









Table 5-1 Test results




X direction



Y direction



Displacement Orbit



5-2 Consideration

The Absver used for this vibration shaking test was made of two bearings of marble and two ball bearings, but standard should be used in combination with two ball bearings as ball bearing as shown in Photo 5-3 , It was confirmed that the response acceleration decreased from the free vibration experiment result, so we chose this combination as the standard.



Photo 5-3

Also, from the vibration table test results, we will infer the response acceleration by the following method.

Figure 5-4 shows the results of the vibration with the same specification as the shaking table test, and Figure 5-5 shows the addition of the vibration reduction pad in Figure 5-4.

When comparing the acceleration of the initial wave and the acceleration of the second wave in free vibration

In Figure 5-4

First time $105/132 = 0.80$ Second time $165/218 = 0.76$ Average 0.78

In Figure 5-5

First time $70/100 = 0.70$ Second time $88/126 = 0.70$ Average 0.7

Although the average reduction in free vibration was about 10%, the results of reflecting the results in the shaking table test are added in Table 5-1.




Fig. 5-4




Fig. 5-5

6. Displacement Analysis by Building

Based on the test at Urban Renaissance Agency, the maximum displacement amount of the building and the seismic isolation device was obtained by our original analysis program.

6-1. Analysis method

As shown in Fig. 6-1, the building was made a vibration model of one mass point by rigidity and damping elements.

We calculated the response acceleration when the ground was forcibly excited with seismic waves measured by the Kobe Marine Weather Valley during the Hyogo ken Nanbu Earthquake and calculated again as the input wave.

In Fig. 6-1, the stiffness is determined so that the mass point M is the effective vibration mass of the building and the natural period calculated from the height of the building matches the natural period calculated from the following formula.

Reinforced Concrete construction : $T = 0.02 \times H$

Steel construction : $T = 0.03 \times H$




Fig. 6-1 One mass vibration model

H: Overall height of building (m)

T: Primary natural period (sec)

M: Vibration mass (weight)

K: Stiffness (restoring force, spring constant)

C: Damping coefficient (braking force)

6-2. Analysis parameters

The details of the building used for this analysis are decided as follows, S-construction is shown in Table 6-1 and RC-construction is summarized in Table 6-2.

- Building height is calculated assuming that the height of the first floor is 3.5 m.
- 2/3 of the building height shall be effective height.
- Determine the weight of the entire building with the plan dimension of the building set to 50 m × 50 m and the weight to 1 tonf / m² to the rank multiple
- S-construction is 0.6 times, R- construction is 0.7 times to the total weight to be the vibration weight.
- Structural attenuation is set so that the response displacement with respect to effective height is 1/100 in S structure and 0.7 / 100 in RC construction.

Table 6-1 Analytical terms of S-construction model

	Building height(m)	Effective height(m)	Weight (tonf)	Primary natural period(s)	Structural decay(%)
10F	3.5	2.33	15000	1.05	19
15F	5.25	3.5	22500	1.575	9
20F	7.0	4.67	30000	2.1	2
30F	10.5	6.8	45000	3.15	2
40F	14.0	9.33	60000	4.2	2

Table 6-2 Analytical terms of RC-construction model

	Building height(m)	Effective height(m)	Weight (tonf)	Primary natural period(s)	Structural decay(%)
10F	3.5	2.33	17500	0.7	12
15F	5.25	3.5	26250	1.05	18
20F	7.0	4.67	35000	1.4	1
30F	10.5	6.8	52500	2.1	1
40F	14.0	9.33	70000	2.8	1

The following three types of Absorber bearings are used for this analysis.

- Standard type
2 marbles + 2 steel balls with earthquake resistant pad
- Earthquake pad change type
Size change of standard earthquake resistant pad
- Marble type
4 marbles




Fig. 6-2 Standard type of Absorber

6-3. Analysis result

For each relative displacement due to building response at the time of earthquake, select a combination of bearings that optimizes the characteristics of Absverer.

The analysis results are shown in the table below.

Table 6-3 Response displacement of S-construction

		Maxi.disp. of building (cm)	Disp. of Absverer (cm)
10F	High floor	23.2	26.3
	Low floor	16.6	13.1
15F	High floor	34.1	30.0
	Low floor	17.1	17.7
20F	High floor	41.0	30
	Mid. floor	27.3	23.8
	Low floor	13.7	10.9
30F	High floor	39.4	13.9
	Mid. floor	26.3	9.3
	Low floor	13.1	5.0
40F	High floor	53.3	14.0
	Mid. floor	35.5	9.3
	Low floor	17.6	4.8

Table 6-4 Response displacement of RC-construction

		Maxi.disp. of building (cm)	Disp. of Absverer (cm)
10F	High floor	16.1	27.2
	Low floor	8.1	13.6
15F	High floor	24.0	27.1
	Low floor	12.0	13.6
20F	High floor	21.5	30
	Mid. floor	11.7	30.0
	Low floor	10.8	12.9
30F	High floor	38.7	26.8
	Mid. floor	25.8	19.3
	Low floor	12.9	10.5
40F	High floor	41.3	18.6
	Mid. floor	27.5	12.4
	Low floor	13.8	6.6

6-4. Summary

We conducted performance evaluation of Absolver with building structure type and installation floor, but in this experiment various assumptions are used to set the building as vibration model of one mass point.

For actual installation, it is desirable to analyze using seismic waves considering ground characteristics etc.

For buildings with heights of 60 m or more, high-rise evaluation is essential and it is necessary to conduct vibration analysis.

